



## BEARING DE MEXICO, S.A. DE C.V.

2 Inch | 50.8 Millimeter x 2.189 Inch | 55.601  
Millimeter x 2.5 Inch | 63.5 Millimeter NTN  
UCP211-200D1 Pillow Block Bearings



UCP211-200D1 Bearing 2D drawings and 3D CAD models

Bearing No. UCP211-200D1

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0
EAN	4547359503357
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	UC211-200D1
Seals	Single Lip Land Riding
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row   Light Duty   Wide Inner Race   Has Flinger
Long Description	2 Bolt Pillow Block; 2" Bore; 2-1/2" Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable;



## BEARING DE MEXICO,S.A.DE C.V.

	Cast Iron; Single Lip Land Riding; Non-expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	UCP211-200D1
Weight / LBS	7.7
Nominal Bolt Center to Center	6.8 Inch   172.7 Millimeter
Actual Bolt Center to Center	6.7 Inch   170.2 Millimeter
d	2 Inch   50.8 Millimeter
B	2.5 Inch   63.5 Millimeter
D	2.189 Inch   55.601 Millimeter
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bore diameter:	2.0000 in
overall width:	2.189 in
bore type:	Round
radial dynamic load capacity:	9750 lb
base to bore centerline:	2.5000 in
radial static load capacity:	6570 lb
duty type:	Light Duty
base width:	2-3/8 in
housing material:	Cast Iron
bolt center-to-center length:	6-23/32 in
locking device:	Set Screw
lubrication type:	Lubrication Fitting



## BEARING DE MEXICO, S.A. DE C.V.

seal type:	Contact with Flinger
series:	UCP2
expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing:	UC211-200D1
overall length:	8.6250 in
standards met:	ANSI, ISO, AFBMA
overall height:	4.9688 in